

Bucket attributes

Through this tab, you can manage the bucket-level attributes. Attributes that can be added as bucket-level attributes are the ones that do not belong to the request attributes or the attribute group assigned to the catalog. You can also manage the vetting lists for those attributes.

The tab appears as shown in the below example:

| Id | Attribute Id | Attribute Name | System Name | Status | Attribute Type Id | Actions |
|----|--------------|------------------------------|------------------------|----------|-------------------|---------|
| 2 | 160 | Units | rasha_att | Inactive | 1 | ⋮ |
| 4 | 162 | Units | Units | Active | 2 | ⋮ |
| 3 | 161 | Risk level | risklevel | Active | 1 | ⋮ |
| 1 | 137 | PLN:Comp Style Bucket (SS20) | Comp_Style_Bucket_SS20 | Active | 1 | ⋮ |

Bucket attributes are listed, for each one, the attribute Id, system name, status, attribute type Id and name, as well as the user who updated the record, and update date are displayed. You can assign a bucket attribute, manage the attribute vetting list, delete, or activate any of the attributes as mentioned in the coming sections.



To assign a bucket attribute, click , the following window appears:

Edit Record ×

Attribute Id

PLN:Comp Style Bucket (SS20) × Risk level ×

CANCEL SAVE

Select the attribute you want then click **Save**.